

## summary for network NT31

timeperiod chosen: from 2024-12-20-00:00:00 until 2024-12-20-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 1.0 seconds


average fixing percentage with threshold set to 0.3: 78.0 percent

stations available: 7 of 7


station information:

station FUER:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 76.887
station LALA:	antenna: TRM59900.00	SCIS	receiver: TRIMBLE NETR9	height: 62.306
station LZ01:	antenna: TRM59800.00	SCIS	receiver: TRIMBLE NETR9	height: 52.693
station LZ02:	antenna: LEIAR20	NONE	receiver: LEICA GR25	height: 58.039
station LZ03:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 314.762
station MASP:	antenna: TRM59900.00	SCIS	receiver: TRIMBLE NETR9	height: 198.846
station ULP2:	antenna: TRM59900.00	SCIS	receiver: TRIMBLE NETR9	height: 375.129


# Processing rate in network NT31




Histogram of the processing rate in network NT31 (durations larger 15 seconds neglected)




Network NT31 with threshold set to 0.3




Fixing percentage of satellites in network NT31 with threshold set to 0.3




Network NT31 - only GPS with threshold set to 0.3



Network NT31 - only GLONASS with threshold set to 0.3




Network NT31 - only BDS with threshold set to 0.3







Network NT31 - only Galileo with threshold set to 0.3




Station FUER in network NT31




Station LALA in network NT31




Station LZ01 in network NT31




Station LZ02 in network NT31



Station LZ03 in network NT31




Station MASP in network NT31




GPS time, starting on DOY 355 of Year 2024

Station ULP2 in network NT31







RefCheck for station FUER in network NT31




RefCheck for station LALA in network NT31




RefCheck for station LZ01 in network NT31




RefCheck for station LZ02 in network NT31




RefCheck for station LZ03 in network NT31



RefCheck for station MASP in network NT31



RefCheck for station ULP2 in network NT31



## RefCheck values for network NT31

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
FUER	-0.015	0.018	0.005	-0.052	0.047	0.019	-0.049	0.12	0.039	0.011	0.023	79505	92.4	84058	97.7
LALA	-0.023	0.021	0.007	-0.036	0.049	0.017	-0.18	0.049	0.029	0.012	0.019	83025	96.5	84793	98.6
LZ01	-0.104	0.085	0.03	-0.123	0.099	0.043	-0.2	0.152	0.062	0.027	0.045	72092	83.8	71041	82.6
LZ02	-0.031	0.02	0.007	-0.03	0.095	0.018	-0.055	0.025	0.012	0.011	0.011	82854	96.3	82488	95.9
LZ03	-0.025	0.014	0.006	-0.054	0.034	0.021	-0.025	0.131	0.041	0.008	0.033	83444	97.0	82728	96.2
MASP	-0.014	0.021	0.006	-0.021	0.062	0.019	-0.02	0.11	0.033	0.014	0.018	85270	99.1	85509	99.4
ULP2	-0.015	0.02	0.006	-0.022	0.065	0.021	-0.032	0.099	0.033	0.015	0.017	84053	97.7	84024	97.7
<b>Mean</b>	-0.032	0.028	0.01	-0.048	0.064	0.023	-0.08	0.098	0.036	0.014	0.024	81463.3	94.7	82091.6	95.4
<b>Min/Max</b>	-0.104	0.085	0.03	-0.123	0.099	0.043	-0.2	0.152	0.062	0.027	0.045	85270	99.1	85509	99.4



## fixing statistic for network NT31

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	78.0	72.8	66.9	91.8	77.6
considering satellites with dual-frequency fixed	71.8	65.3	61.4	89.1	70.8
considering all signals separately	73.2	65.5	61.4	89.7	69.4