

summary for network NT32

timeperiod chosen: from 2025-05-28-00:00:00 until 2025-05-28-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 1.2 seconds


average fixing percentage with threshold set to 0.3: 90.6 percent

stations available: 15 of 16


station information:

station EH01:	antenna: LEIAR20	LEIM	receiver: LEICA GR25	height: 801.016
station EH02:	antenna: TRM59900.00	SCIS	receiver: TRIMBLE NETR9	height: 85.364
station GOM1:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 48.789
station IZAN:	antenna: LEIAT504GG	LEIS	receiver: LEICA GR50	height: 2417.44
station LP01:	antenna: TRM57971.00	NONE	receiver: TRIMBLE ALLOY	height: 675.249
station LP03:	antenna: TRM59900.00	NONE	receiver: TRIMBLE NETR9	height: 919.563
station LPAL:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 2199.31
station LRES:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 51.241
station TN01:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 51.859
station TN02:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 54.509
station TN03:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 58.588
station TN04:	antenna: LEIAT504	LEIS	receiver: LEICA GR50	height: 1468.105
station TN06:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1053.548
station TN09:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1582.15
station TE11:	antenna: LEIAR10	NONE	receiver: LEICA GR25	height: 2092.021


Processing rate in network NT32




Histogram of the processing rate in network NT32 (durations larger 15 seconds neglected)




Network NT32 with threshold set to 0.3




Fixing percentage of satellites in network NT32 with threshold set to 0.3




Network NT32 - only GPS with threshold set to 0.3




Network NT32 - only GLONASS with threshold set to 0.3




Network NT32 - only BDS with threshold set to 0.3




Network NT32 - only Galileo with threshold set to 0.3




Station EH01 in network NT32




Station EH02 in network NT32




Station GOM1 in network NT32




Station IZAN in network NT32




Station LP01 in network NT32




Station LP03 in network NT32




Station LPAL in network NT32




Station LRES in network NT32




Station TN01 in network NT32




Station TN02 in network NT32




Station TN03 in network NT32




Station TN04 in network NT32




Station TN06 in network NT32




Station TN09 in network NT32




Station TE11 in network NT32




RefCheck for station EH01 in network NT32




RefCheck for station EH02 in network NT32




RefCheck for station GOM1 in network NT32




RefCheck for station IZAN in network NT32




RefCheck for station LP01 in network NT32




RefCheck for station LP03 in network NT32




RefCheck for station LPAL in network NT32




RefCheck for station LRES in network NT32




RefCheck for station TN01 in network NT32




RefCheck for station TN02 in network NT32




RefCheck for station TN03 in network NT32




RefCheck for station TN04 in network NT32




RefCheck for station TN06 in network NT32



RefCheck for station TN09 in network NT32



RefCheck for station TE11 in network NT32



RefCheck values for network NT32

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
EH01	-0.014	0.009	0.003	-0.001	0.024	0.004	-0.017	0.04	0.011	0.004	0.007	66700	92.5	24425	33.9
EH02	-0.008	0.015	0.004	-0.001	0.024	0.004	-0.002	0.046	0.009	0.004	0.008	68062	94.3	52755	73.1
GOM1	-0.01	0.011	0.004	-0.021	0.001	0.004	-0.025	0.018	0.009	0.004	0.005	33977	46.2	10042	13.7
IZAN	-0.01	0.013	0.003	-0.012	0.007	0.003	-0.059	0.022	0.011	0.003	0.008	6654	9.1	5406	7.4
LP01	-0.015	0.001	0.003	-0.002	0.014	0.003	-0.003	0.024	0.006	0.003	0.005	55331	76.7	14798	20.5
LP03	-0.012	0.009	0.003	-0.012	0.015	0.004	-0.047	0.023	0.013	0.003	0.009	7023	9.7	9565	13.3
LPAL	-0.014	0.0	0.003	-0.001	0.017	0.003	-0.015	0.027	0.007	0.003	0.004	59083	80.4	1558	2.1
LRES	-0.005	0.011	0.003	-0.0	0.022	0.004	-0.02	0.021	0.009	0.004	0.005	60136	83.4	15366	21.3
TN01	-0.016	0.005	0.003	-0.017	0.003	0.003	-0.023	0.018	0.008	0.003	0.004	36362	50.4	3506	4.9
TN02	-0.015	0.027	0.006	-0.029	0.016	0.005	-0.08	0.043	0.021	0.005	0.013	16835	23.3	32436	45.0
TN03	-0.009	0.017	0.004	-0.01	0.006	0.003	-0.046	0.021	0.012	0.003	0.009	5655	7.8	10455	14.5
TN04	-0.013	0.012	0.004	-0.018	0.005	0.004	-0.027	0.021	0.009	0.004	0.006	13887	19.2	8900	12.3
TN06	-0.009	0.002	0.002	-0.009	0.004	0.002	-0.014	0.009	0.005	0.002	0.003	0	0.0	0	0.0
TN09	-0.001	0.022	0.003	-0.013	0.0	0.002	-0.018	0.02	0.007	0.003	0.004	34457	47.8	3948	5.5
TE11	-0.015	0.019	0.005	-0.022	0.004	0.004	-0.05	0.035	0.013	0.005	0.009	16162	22.4	13153	18.2
Mean	-0.011	0.012	0.004	-0.011	0.011	0.003	-0.03	0.026	0.01	0.004	0.007	32021.6	44.2	13754.2	19.0
Min/Max	-0.016	0.027	0.006	-0.029	0.024	0.005	-0.08	0.046	0.021	0.005	0.013	68062	94.3	52755	73.1

fixing statistic for network NT32

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	90.6	91.3	89.8	91.6	89.5
considering satellites with dual-frequency fixed	86.5	87.6	82.0	88.1	87.2
considering all signals separately	86.5	87.3	82.0	88.2	85.8