

## summary for network N32T

timeperiod chosen: from 2025-01-22-00:00:00 until 2025-01-22-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 1.7 seconds


average fixing percentage with threshold set to 0.3: 81.8 percent

stations available: 12 of 16


station information:

station GOM1:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 48.789
station IZAN:	antenna: LEIAT504GG	LEIS	receiver: LEICA GR50	height: 2417.44
station LP01:	antenna: TRM57971.00	NONE	receiver: TRIMBLE ALLOY	height: 675.249
station LP03:	antenna: TRM59900.00	NONE	receiver: TRIMBLE NETR9	height: 919.563
station LPAL:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 2199.31
station TN01:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 51.859
station TN02:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 54.509
station TN03:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 58.588
station TN04:	antenna: LEIAT504	LEIS	receiver: LEICA GR50	height: 1468.105
station TN06:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1053.548
station TN09:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1582.15
station TE11:	antenna: LEIAR10	NONE	receiver: LEICA GR25	height: 2092.021


Processing rate in network N32T




Histogram of the processing rate in network N32T (durations larger 15 seconds neglected)




Network N32T with threshold set to 0.3




Fixing percentage of satellites in network N32T with threshold set to 0.3




Network N32T - only GPS with threshold set to 0.3



Network N32T - only GLONASS with threshold set to 0.3




Network N32T - only BDS with threshold set to 0.3







Network N32T - only Galileo with threshold set to 0.3




Station GOM1 in network N32T




Station IZAN in network N32T




Station LP01 in network N32T




Station LP03 in network N32T




Station LPAL in network N32T



Station TN01 in network N32T




Station TN02 in network N32T







Station TN03 in network N32T




Station TN04 in network N32T




Station TN06 in network N32T




Station TN09 in network N32T




Station TE11 in network N32T




# RefCheck for station GOM1 in network N32T



RefCheck for station IZAN in network N32T




RefCheck for station LP01 in network N32T







RefCheck for station LP03 in network N32T




# RefCheck for station LPAL in network N32T




RefCheck for station TN01 in network N32T




RefCheck for station TN02 in network N32T




# RefCheck for station TN03 in network N32T




### RefCheck for station TN04 in network N32T



# RefCheck for station TN06 in network N32T




RefCheck for station TN09 in network N32T





# RefCheck for station TE11 in network N32T



## RefCheck values for network N32T

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
GOM1	-0.021	0.017	0.004	-0.013	0.019	0.004	-0.046	0.041	0.013	0.004	0.01	4125	10.1	10482	25.8
IZAN	-0.014	0.011	0.004	-0.008	0.012	0.004	-0.048	0.022	0.012	0.002	0.006	3435	8.5	4750	11.7
LP01	-0.02	0.015	0.005	-0.014	0.034	0.006	-0.071	0.045	0.023	0.006	0.013	24634	60.6	26608	65.5
LP03	-0.038	0.012	0.006	-0.013	0.014	0.004	-0.029	0.11	0.02	0.006	0.018	10912	26.8	12427	30.6
LPAL	-0.018	0.02	0.004	-0.012	0.023	0.006	-0.046	0.052	0.016	0.005	0.009	33652	82.8	20231	49.8
TN01	-0.054	0.017	0.011	-0.041	0.008	0.01	-0.06	0.033	0.022	0.013	0.018	13790	33.9	18333	45.1
TN02	-0.015	0.011	0.003	-0.011	0.018	0.003	-0.009	0.077	0.013	0.002	0.011	1517	3.7	31754	78.1
TN03	-0.008	0.006	0.002	-0.008	0.008	0.004	-0.025	0.015	0.009	0.002	0.005	63	0.2	1753	4.3
TN04	-0.003	0.011	0.003	-0.012	0.005	0.004	-0.014	0.031	0.01	0.003	0.005	4571	11.2	2361	5.8
TN06	-0.037	0.007	0.007	-0.013	0.016	0.004	-0.083	0.018	0.029	0.006	0.024	13854	34.1	25654	63.1
TN09	-0.007	0.026	0.004	-0.019	0.01	0.004	-0.041	0.038	0.011	0.003	0.005	19621	48.3	3563	8.8
TE11	-0.012	0.011	0.003	-0.011	0.006	0.002	-0.037	0.113	0.023	0.003	0.02	1688	4.2	4251	10.5
<b>Mean</b>	<b>-0.021</b>	<b>0.014</b>	<b>0.005</b>	<b>-0.015</b>	<b>0.014</b>	<b>0.005</b>	<b>-0.042</b>	<b>0.05</b>	<b>0.017</b>	<b>0.005</b>	<b>0.012</b>	<b>10988.5</b>	<b>27.0</b>	<b>13513.9</b>	<b>33.3</b>
<b>Min/Max</b>	<b>-0.054</b>	<b>0.026</b>	<b>0.011</b>	<b>-0.041</b>	<b>0.034</b>	<b>0.01</b>	<b>-0.083</b>	<b>0.113</b>	<b>0.029</b>	<b>0.013</b>	<b>0.024</b>	<b>33652</b>	<b>82.8</b>	<b>31754</b>	<b>78.1</b>

fixing statistic for network N32T

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	81.8	84.7	75.5	84.1	80.8
considering satellites with dual-frequency fixed	72.3	75.9	63.4	76.1	70.9
considering all signals separately	72.4	75.3	63.4	76.5	68.8