

summary for network NT10

timeperiod chosen: from 2025-09-08-00:00:00 until 2025-09-08-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 1.4 seconds


average fixing percentage with threshold set to 0.3: 91.7 percent

stations available: 15 of 16


station information:

station BCL1:	antenna: LEIAR20	LEIM	receiver: LEICA GR25	height: 56.129
station BCLN:	antenna: LEIAR25.R4	LEIT	receiver: LEICA GR10	height: 84.875
station BELL:	antenna: LEIAR25.R4	NONE	receiver: LEICA GR50	height: 853.488
station BINE:	antenna: GPPNULLANTENNA	NONE	receiver: LEICA GR50	height: 346.97
station CREU:	antenna: LEIAR25.R4	NONE	receiver: LEICA GR50	height: 133.464
station EBRE:	antenna: LEIAR25.R4	NONE	receiver: LEICA GR50	height: 107.868
station EBRO:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 54.387
station ESCO:	antenna: LEIAR25.R4	NONE	receiver: LEICA GR50	height: 2508.504
station GRAU:	antenna: GPPNULLANTENNA	NONE	receiver: TPS NET-G3	height: 509.777
station MEQU:	antenna: GPPNULLANTENNA	NONE	receiver: LEICA GR50	height: 138.594
station OLOT:	antenna: TRM57971.00	TZGD	receiver: LEICA GR25	height: 600.533
station PUIG:	antenna: TRM59900.00	SCIS	receiver: TRIMBLE NETR9	height: 1162.395
station TARR:	antenna: LEIAR20	LEIM	receiver: LEICA GR25	height: 491.514
station TRRG:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 55.163
station VRO2:	antenna: GPPNULLANTENNA	NONE	receiver: LEICA GR50	height: 541.427


Processing rate in network NT10




Histogram of the processing rate in network NT10 (durations larger 15 seconds neglected)




Network NT10 with threshold set to 0.3




Fixing percentage of satellites in network NT10 with threshold set to 0.3




Network NT10 - only GPS with threshold set to 0.3




Network NT10 - only GLONASS with threshold set to 0.3




Network NT10 - only BDS with threshold set to 0.3




Network NT10 - only Galileo with threshold set to 0.3




Station BCL1 in network NT10




Station BCLN in network NT10




Station BELL in network NT10




Station BINE in network NT10




Station CREU in network NT10



Station EBRE in network NT10




Station EBRO in network NT10




Station ESCO in network NT10




Station GRAU in network NT10




Station MEQU in network NT10




Station OLOT in network NT10




Station PUIG in network NT10




Station TARR in network NT10




Station TRRG in network NT10




Station VRO2 in network NT10




RefCheck for station BCL1 in network NT10




RefCheck for station BCLN in network NT10




RefCheck for station BELL in network NT10




RefCheck for station BINE in network NT10




RefCheck for station CREU in network NT10




RefCheck for station EBRE in network NT10




RefCheck for station EBRO in network NT10




RefCheck for station ESCO in network NT10




RefCheck for station GRAU in network NT10




RefCheck for station MEQU in network NT10




RefCheck for station OLOT in network NT10




RefCheck for station PUIG in network NT10




RefCheck for station TARR in network NT10



RefCheck for station TRRG in network NT10



RefCheck for station VRO2 in network NT10



RefCheck values for network NT10

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
BCL1	-0.025	0.009	0.005	-0.011	0.01	0.004	-0.04	0.011	0.01	0.004	0.007	11996	19.7	17154	28.2
BCLN	-0.016	0.012	0.006	-0.02	0.007	0.005	-0.013	0.036	0.009	0.004	0.007	22009	36.2	5678	9.3
BELL	-0.028	0.021	0.006	-0.022	0.018	0.004	-0.009	0.047	0.01	0.004	0.009	6742	11.1	10225	16.8
BINE	-0.055	0.023	0.005	-0.027	0.024	0.007	-0.039	0.039	0.011	0.005	0.008	14272	23.5	7955	13.1
CREU	-0.017	0.007	0.005	-0.017	0.009	0.004	-0.025	0.022	0.008	0.003	0.005	8161	13.4	1822	3.0
EBRE	-0.042	0.047	0.007	-0.02	0.035	0.005	-0.044	0.049	0.009	0.005	0.007	21848	35.9	6739	11.1
EBRO	-0.02	0.041	0.008	-0.022	0.027	0.005	-0.041	0.031	0.011	0.005	0.007	31651	52.0	12680	20.8
ESCO	-0.024	0.02	0.006	-0.018	0.011	0.004	-0.033	0.05	0.012	0.004	0.008	8818	14.5	7467	12.3
GRAU	-0.024	0.018	0.007	-0.025	0.016	0.006	-0.032	0.028	0.012	0.005	0.007	24409	40.1	11668	19.2
MEQU	-0.023	0.012	0.004	-0.027	0.004	0.003	-0.042	0.032	0.013	0.003	0.007	12513	20.6	11397	18.7
OLOT	-0.024	0.029	0.008	-0.028	0.028	0.005	-0.036	0.015	0.011	0.005	0.008	15253	25.1	14255	23.4
PUIG	-0.024	0.025	0.006	-0.011	0.015	0.004	-0.042	0.028	0.01	0.004	0.007	17782	29.2	8055	13.2
TARR	-0.022	0.008	0.005	-0.022	0.012	0.004	-0.039	0.02	0.011	0.005	0.008	16965	27.9	8293	13.6
TRRG	-0.027	0.023	0.008	-0.025	0.011	0.005	-0.043	0.032	0.012	0.005	0.007	48478	79.7	20713	34.0
VRO2	-0.022	0.03	0.007	-0.024	0.025	0.005	-0.024	0.051	0.011	0.005	0.007	19012	31.3	7606	12.5
Mean	-0.026	0.022	0.006	-0.021	0.017	0.005	-0.033	0.033	0.011	0.004	0.007	18660.6	30.7	10113.8	16.6
Min/Max	-0.055	0.047	0.008	-0.028	0.035	0.007	-0.044	0.051	0.013	0.005	0.009	48478	79.7	20713	34.0

fixing statistic for network NT10

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	91.7	93.2	92.1	92.5	89.0
considering satellites with dual-frequency fixed	89.2	89.6	88.5	90.4	87.7
considering all signals separately	89.5	89.8	88.5	90.8	87.3