

summary for network N32T

timeperiod chosen: from 2025-09-19-00:00:00 until 2025-09-19-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 2.0 seconds


average fixing percentage with threshold set to 0.3: 85.1 percent

stations available: 15 of 16


station information:

station EH01:	antenna: LEIAR20	LEIM	receiver: LEICA GR25	height: 801.016
station EH02:	antenna: TRM59900.00	SCIS	receiver: TRIMBLE NETR9	height: 85.364
station GOM1:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 48.789
station GOME:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 114.977
station IZAN:	antenna: LEIAT504GG	LEIS	receiver: LEICA GR50	height: 2417.44
station LP01:	antenna: TRM57971.00	NONE	receiver: TRIMBLE ALLOY	height: 675.249
station LP03:	antenna: TRM59900.00	NONE	receiver: TRIMBLE NETR9	height: 919.563
station LPAL:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 2199.31
station LRES:	antenna: LEIAR20	NONE	receiver: LEICA GR25	height: 51.241
station TN01:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 51.859
station TN02:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 54.509
station TN03:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 58.588
station TN04:	antenna: LEIAT504	LEIS	receiver: LEICA GR50	height: 1468.105
station TN06:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1053.548
station TN09:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1582.15
station TE11:	antenna: LEIAR10	NONE	receiver: LEICA GR25	height: 2092.021


Processing rate in network N32T




Histogram of the processing rate in network N32T (durations larger 15 seconds neglected)




Network N32T with threshold set to 0.3




Fixing percentage of satellites in network N32T with threshold set to 0.3




Network N32T - only GPS with threshold set to 0.3




Network N32T - only GLONASS with threshold set to 0.3




Network N32T - only BDS with threshold set to 0.3




Network N32T - only Galileo with threshold set to 0.3




Station EH01 in network N32T




Station GOM1 in network N32T




Station GOME in network N32T




Station IZAN in network N32T




Station LP01 in network N32T




Station LP03 in network N32T




Station LPAL in network N32T




Station LRES in network N32T




Station TN01 in network N32T




Station TN02 in network N32T




Station TN03 in network N32T




Station TN04 in network N32T




Station TN06 in network N32T




Station TN09 in network N32T




Station TE11 in network N32T




RefCheck for station EH01 in network N32T




RefCheck for station GOM1 in network N32T




RefCheck for station GOME in network N32T




RefCheck for station IZAN in network N32T




RefCheck for station LP01 in network N32T




RefCheck for station LP03 in network N32T




RefCheck for station LPAL in network N32T




RefCheck for station LRES in network N32T




RefCheck for station TN01 in network N32T




RefCheck for station TN02 in network N32T




RefCheck for station TN03 in network N32T




RefCheck for station TN04 in network N32T




RefCheck for station TN06 in network N32T



RefCheck for station TN09 in network N32T



RefCheck for station TE11 in network N32T



RefCheck values for network N32T

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
EH01	-0.025	0.015	0.005	-0.018	0.027	0.009	-0.015	0.018	0.006	0.004	0.004	41161	93.4	7857	17.8
GOM1	-0.011	0.004	0.003	-0.018	0.029	0.004	-0.018	0.008	0.005	0.003	0.004	25069	56.9	1250	2.8
GOME	-0.009	0.026	0.004	-0.009	0.015	0.003	-0.014	0.024	0.006	0.003	0.005	2181	5.0	2595	5.9
IZAN	-0.009	0.006	0.002	-0.013	0.004	0.003	-0.019	0.011	0.005	0.002	0.004	2060	4.7	159	0.4
LP01	-0.019	0.007	0.004	-0.007	0.015	0.004	0.002	0.026	0.005	0.002	0.004	39512	89.7	11892	27.0
LP03	-0.011	0.009	0.003	-0.004	0.014	0.003	-0.006	0.021	0.006	0.003	0.004	3968	9.0	2215	5.0
LPAL	-0.019	-0.001	0.003	-0.003	0.019	0.003	-0.013	0.014	0.006	0.003	0.003	41111	93.3	1619	3.7
LRES	-0.006	0.021	0.004	-0.011	0.028	0.005	-0.053	0.019	0.013	0.004	0.009	39073	88.7	13131	29.8
TN01	-0.013	0.007	0.003	-0.021	-0.004	0.003	-0.026	0.003	0.007	0.003	0.005	17495	39.7	9022	20.5
TN02	-0.009	0.008	0.003	-0.019	0.004	0.004	-0.007	0.026	0.007	0.003	0.006	4610	10.5	6845	15.5
TN03	-0.011	0.011	0.003	-0.009	0.007	0.003	-0.031	0.014	0.007	0.002	0.005	321	0.7	2585	5.9
TN04	-0.022	0.006	0.005	-0.013	0.001	0.002	-0.023	0.005	0.005	0.004	0.005	4894	11.1	3074	7.0
TN06	-0.008	0.01	0.002	-0.013	0.019	0.004	-0.015	0.012	0.005	0.002	0.003	2002	4.5	0	0.0
TN09	0.0	0.015	0.002	-0.017	0.002	0.004	-0.014	0.018	0.006	0.003	0.003	33678	76.5	1652	3.8
TE11	-0.007	0.01	0.003	-0.02	0.001	0.003	-0.014	0.022	0.007	0.003	0.004	9305	21.1	2165	4.9
Mean	-0.012	0.01	0.003	-0.013	0.012	0.004	-0.018	0.016	0.006	0.003	0.005	17762.7	40.3	4404.1	10.0
Min/Max	-0.025	0.026	0.005	-0.021	0.029	0.009	-0.053	0.026	0.013	0.004	0.009	41161	93.4	13131	29.8

fixing statistic for network N32T

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	85.1	85.9	89.4	83.8	85.0
considering satellites with dual-frequency fixed	85.5	85.5	88.7	83.8	84.6
considering all signals separately	85.2	85.4	88.7	84.1	83.9