

summary for network N32T

timeperiod chosen: from 2025-10-22-00:00:00 until 2025-10-22-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 1.4 seconds


average fixing percentage with threshold set to 0.3: 80.3 percent

stations available: 15 of 16


station information:

station EH01:	antenna: LEIAR20	LEIM	receiver: LEICA GR25	height: 801.016
station GOM1:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 48.789
station GOME:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 114.977
station IZAN:	antenna: LEIAT504GG	LEIS	receiver: LEICA GR50	height: 2417.44
station LP01:	antenna: TRM57971.00	NONE	receiver: TRIMBLE ALLOY	height: 675.249
station LP03:	antenna: TRM59900.00	NONE	receiver: TRIMBLE NETR9	height: 919.563
station LPAL:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 2199.31
station LRES:	antenna: LEIAR20	NONE	receiver: LEICA GR25	height: 51.241
station TN01:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 51.859
station TN02:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 54.509
station TN03:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 58.588
station TN04:	antenna: LEIAT504	LEIS	receiver: LEICA GR50	height: 1468.105
station TN06:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1053.548
station TN09:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1582.15
station TE11:	antenna: LEIAR10	NONE	receiver: LEICA GR25	height: 2092.021


Processing rate in network N32T




Histogram of the processing rate in network N32T (durations larger 15 seconds neglected)




Network N32T with threshold set to 0.3




Fixing percentage of satellites in network N32T with threshold set to 0.3




Network N32T - only GPS with threshold set to 0.3




Network N32T - only GLONASS with threshold set to 0.3




Network N32T - only BDS with threshold set to 0.3




Network N32T - only Galileo with threshold set to 0.3




Station EH01 in network N32T




Station GOM1 in network N32T




Station GOME in network N32T




Station IZAN in network N32T




Station LP01 in network N32T




Station LP03 in network N32T




Station LPAL in network N32T




Station LRES in network N32T




Station TN01 in network N32T




Station TN02 in network N32T




Station TN03 in network N32T




Station TN04 in network N32T




Station TN06 in network N32T




Station TN09 in network N32T




Station TE11 in network N32T




RefCheck for station EH01 in network N32T




RefCheck for station GOM1 in network N32T




RefCheck for station GOME in network N32T




RefCheck for station IZAN in network N32T




RefCheck for station LP01 in network N32T




RefCheck for station LP03 in network N32T




RefCheck for station LPAL in network N32T




RefCheck for station LRES in network N32T




RefCheck for station TN01 in network N32T




RefCheck for station TN02 in network N32T




RefCheck for station TN03 in network N32T




RefCheck for station TN04 in network N32T




RefCheck for station TN06 in network N32T



RefCheck for station TN09 in network N32T



RefCheck for station TE11 in network N32T



RefCheck values for network N32T

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
EH01	-0.018	0.014	0.005	-0.005	0.03	0.005	-0.021	0.035	0.011	0.004	0.006	49970	78.8	16751	26.4
GOM1	-0.014	0.022	0.005	-0.03	0.037	0.006	-0.056	0.06	0.014	0.005	0.009	47975	75.7	16309	25.7
GOME	-0.014	0.025	0.004	-0.049	0.028	0.008	-0.056	0.06	0.013	0.007	0.01	14529	22.9	12169	19.2
IZAN	-0.022	0.026	0.005	-0.02	0.012	0.004	-0.045	0.027	0.009	0.005	0.007	28336	44.7	10884	17.2
LP01	-0.029	0.003	0.005	-0.028	0.028	0.008	-0.035	0.036	0.014	0.005	0.008	46865	73.9	26611	42.0
LP03	-0.022	0.017	0.005	-0.013	0.047	0.009	-0.06	0.06	0.016	0.007	0.012	20020	31.6	17709	27.9
LPAL	-0.026	0.039	0.006	-0.036	0.028	0.007	-0.038	0.072	0.016	0.007	0.011	46223	72.9	26635	42.0
LRES	-0.009	0.058	0.005	-0.008	0.027	0.006	-0.034	0.016	0.009	0.005	0.005	52549	82.9	13255	20.9
TN01	-0.013	0.012	0.003	-0.031	0.012	0.006	-0.034	0.021	0.009	0.004	0.008	46548	73.4	21649	34.2
TN02	-0.015	0.026	0.005	-0.024	0.013	0.007	-0.06	0.034	0.011	0.005	0.009	23505	37.1	12705	20.0
TN03	-0.029	0.028	0.006	-0.027	0.014	0.006	-0.035	0.027	0.011	0.005	0.007	18115	28.6	14022	22.1
TN04	-0.007	0.015	0.004	-0.015	0.014	0.005	-0.031	0.026	0.01	0.004	0.006	20854	32.9	9401	14.8
TN06	-0.023	0.013	0.005	-0.027	0.018	0.007	-0.055	0.017	0.011	0.005	0.008	18675	29.5	8829	13.9
TN09	-0.029	0.027	0.007	-0.027	0.009	0.006	-0.028	0.03	0.011	0.005	0.006	56795	89.6	28179	44.5
TE11	-0.016	0.015	0.004	-0.019	0.024	0.007	-0.031	0.037	0.012	0.005	0.007	26800	42.3	9581	15.1
Mean	-0.019	0.023	0.005	-0.024	0.023	0.006	-0.041	0.037	0.012	0.005	0.008	34517.3	54.5	16312.6	25.7
Min/Max	-0.029	0.058	0.007	-0.049	0.047	0.009	-0.06	0.072	0.016	0.007	0.012	56795	89.6	28179	44.5

fixing statistic for network N32T

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	80.3	84.2	77.4	80.2	78.5
considering satellites with dual-frequency fixed	74.3	78.2	66.4	75.6	73.6
considering all signals separately	74.2	77.5	66.4	75.5	72.2