

summary for network N32T

timeperiod chosen: from 2025-03-29-00:00:00 until 2025-03-29-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 2.2 seconds


average fixing percentage with threshold set to 0.3: 84.3 percent

stations available: 14 of 16


station information:

station EH01:	antenna: LEIAR20	LEIM	receiver: LEICA GR25	height: 801.016
station EH02:	antenna: TRM59900.00	SCIS	receiver: TRIMBLE NETR9	height: 85.364
station GOM1:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 48.789
station IZAN:	antenna: LEIAT504GG	LEIS	receiver: LEICA GR50	height: 2417.44
station LP01:	antenna: TRM57971.00	NONE	receiver: TRIMBLE ALLOY	height: 675.249
station LP03:	antenna: TRM59900.00	NONE	receiver: TRIMBLE NETR9	height: 919.563
station LPAL:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 2199.31
station LRES:	antenna: LEIAR20	NONE	receiver: LEICA GR25	height: 51.241
station TN01:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 51.859
station TN02:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 54.509
station TN03:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 58.588
station TN04:	antenna: LEIAT504	LEIS	receiver: LEICA GR50	height: 1468.105
station TN06:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1053.508
station TN09:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1582.15
station TE11:	antenna: LEIAR10	NONE	receiver: LEICA GR25	height: 2092.021


Processing rate in network N32T




Histogram of the processing rate in network N32T (durations larger 15 seconds neglected)




Network N32T with threshold set to 0.3




Fixing percentage of satellites in network N32T with threshold set to 0.3




Network N32T - only GPS with threshold set to 0.3




Network N32T - only GLONASS with threshold set to 0.3




Network N32T - only BDS with threshold set to 0.3




Network N32T - only Galileo with threshold set to 0.3




Station EH01 in network N32T




Station EH02 in network N32T




Station GOM1 in network N32T




Station IZAN in network N32T




Station LP01 in network N32T




Station LP03 in network N32T




Station LPAL in network N32T




Station LRES in network N32T




Station TN01 in network N32T




Station TN02 in network N32T




Station TN03 in network N32T




Station TN06 in network N32T




Station TN09 in network N32T




Station TE11 in network N32T




RefCheck for station EH01 in network N32T




RefCheck for station EH02 in network N32T




RefCheck for station GOM1 in network N32T




RefCheck for station IZAN in network N32T




RefCheck for station LP01 in network N32T




RefCheck for station LP03 in network N32T




RefCheck for station LPAL in network N32T




RefCheck for station LRES in network N32T




RefCheck for station TN01 in network N32T




RefCheck for station TN02 in network N32T




RefCheck for station TN03 in network N32T




RefCheck for station TN06 in network N32T



RefCheck for station TN09 in network N32T



RefCheck for station TE11 in network N32T



RefCheck values for network N32T

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
EH01	-0.021	0.026	0.007	-0.013	0.028	0.008	-0.032	0.021	0.011	0.006	0.007	26093	67.5	17879	46.2
EH02	-0.017	0.043	0.009	-0.014	0.04	0.007	-0.062	0.052	0.012	0.008	0.01	21213	54.9	10091	26.1
GOM1	-0.031	0.014	0.005	-0.027	0.028	0.006	-0.029	0.028	0.011	0.005	0.007	20938	54.1	8504	22.0
IZAN	-0.017	0.01	0.004	-0.035	0.0	0.007	-0.067	0.01	0.018	0.007	0.017	14220	36.8	10643	27.5
LP01	-0.034	0.001	0.006	-0.008	0.037	0.006	-0.013	0.034	0.008	0.007	0.009	19212	49.7	12939	33.5
LP03	-0.018	0.01	0.005	-0.016	0.035	0.008	-0.025	0.018	0.008	0.006	0.007	6476	16.7	3456	8.9
LPAL	-0.023	0.011	0.004	-0.006	0.02	0.003	-0.028	0.02	0.01	0.004	0.005	11802	30.5	3345	8.7
LRES	-0.012	0.05	0.005	-0.01	0.04	0.005	-0.036	0.024	0.009	0.005	0.006	25093	64.9	8082	20.9
TN01	-0.018	0.022	0.004	-0.034	0.008	0.004	-0.035	0.019	0.01	0.004	0.006	27352	70.7	8737	22.6
TN02	-0.036	0.012	0.006	-0.04	0.035	0.009	-0.03	0.079	0.018	0.007	0.015	14858	38.4	16780	43.4
TN03	-0.016	0.015	0.004	-0.013	0.01	0.003	-0.029	0.026	0.01	0.003	0.006	2080	5.4	3981	10.3
TN06	-0.014	0.009	0.004	-0.032	0.005	0.006	-0.063	0.013	0.013	0.006	0.012	12640	32.7	21649	56.0
TN09	-0.015	0.023	0.007	-0.039	0.007	0.006	-0.043	0.025	0.015	0.007	0.009	20026	51.8	14257	36.9
TE11	-0.029	0.014	0.005	-0.014	0.038	0.007	-0.019	0.073	0.012	0.005	0.009	10342	26.7	3939	10.2
Mean	-0.022	0.019	0.005	-0.022	0.024	0.006	-0.036	0.032	0.012	0.006	0.009	16596.1	42.9	10305.9	26.7
Min/Max	-0.036	0.05	0.009	-0.04	0.04	0.009	-0.067	0.079	0.018	0.008	0.017	27352	70.7	21649	56.0

fixing statistic for network N32T

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	84.3	85.1	77.6	87.8	84.8
considering satellites with dual-frequency fixed	80.0	80.4	71.9	83.3	83.1
considering all signals separately	80.4	80.7	71.9	83.4	82.3