

summary for network N32T

timeperiod chosen: from 2026-07-12-00:00:00 until 2026-07-12-23:59:59

average update rate (durations larger than 15 seconds considered as observation gap): 1.3 seconds


average fixing percentage with threshold set to 0.3: 95.0 percent

stations available: 15 of 15


station information:

station EH01:	antenna: LEIAR20	LEIM	receiver: LEICA GR25	height: 801.016
station EH02:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 85.385
station GOM1:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 48.789
station GOME:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 114.977
station IZAN:	antenna: LEIAT504GG	LEIS	receiver: LEICA GR50	height: 2417.44
station LP01:	antenna: TRM57971.00	NONE	receiver: TRIMBLE ALLOY	height: 675.249
station LP03:	antenna: TRM59900.00	NONE	receiver: TRIMBLE NETR9	height: 919.563
station LPAL:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 2199.31
station LRES:	antenna: LEIAR20	NONE	receiver: LEICA GR25	height: 51.241
station TN01:	antenna: LEIAR20	LEIM	receiver: LEICA GR50	height: 51.859
station TN02:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 54.509
station TN03:	antenna: TRM159900.00	SCIS	receiver: TRIMBLE ALLOY	height: 58.588
station TN06:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1053.548
station TN09:	antenna: LEIAR20	NONE	receiver: LEICA GR50	height: 1582.15
station TE11:	antenna: LEIAR10	NONE	receiver: LEICA GR25	height: 2092.021


Processing rate in network N32T




Histogram of the processing rate in network N32T (durations larger 15 seconds neglected)




Network N32T with threshold set to 0.3




Fixing percentage of satellites in network N32T with threshold set to 0.3




Network N32T - only GPS with threshold set to 0.3




Network N32T - only GLONASS with threshold set to 0.3




Network N32T - only BDS with threshold set to 0.3




Network N32T - only Galileo with threshold set to 0.3




Station EH01 in network N32T




Station EH02 in network N32T




Station GOM1 in network N32T




Station GOME in network N32T




Station IZAN in network N32T




Station LP01 in network N32T




Station LP03 in network N32T




Station LPAL in network N32T



Station LRES in network N32T




Station TN01 in network N32T




Station TN02 in network N32T




Station TN03 in network N32T




Station TN06 in network N32T




Station TN09 in network N32T




Station TE11 in network N32T




RefCheck for station EH01 in network N32T




RefCheck for station EH02 in network N32T




RefCheck for station GOM1 in network N32T




RefCheck for station GOME in network N32T




RefCheck for station IZAN in network N32T




RefCheck for station LP01 in network N32T




RefCheck for station LP03 in network N32T




RefCheck for station LPAL in network N32T




RefCheck for station LRES in network N32T




RefCheck for station TN01 in network N32T




RefCheck for station TN02 in network N32T




RefCheck for station TN03 in network N32T




RefCheck for station TN06 in network N32T



RefCheck for station TN09 in network N32T



RefCheck for station TE11 in network N32T



RefCheck values for network N32T

Station	Nmin	Nmax	Nstd	Emin	Emax	Estd	Umin	Umax	Ustd	std2D	std3D	#2D > 0.01	% 2D > 0.01	#3D > 0.02	% 3D > 0.02
EH01	-0.005	0.011	0.002	-0.0	0.03	0.003	-0.002	0.028	0.006	0.003	0.004	64697	99.8	57093	88.1
EH02	-0.015	0.015	0.004	0.0	0.026	0.003	-0.036	0.02	0.009	0.003	0.004	64694	99.8	57930	89.4
GOM1	-0.012	0.014	0.005	-0.024	0.012	0.006	-0.059	0.015	0.013	0.005	0.009	46223	71.3	28233	43.6
GOME	-0.005	0.016	0.004	-0.007	0.015	0.005	-0.027	0.02	0.009	0.004	0.006	15364	23.7	5945	9.2
IZAN	-0.008	0.007	0.002	-0.018	0.026	0.004	-0.06	0.034	0.009	0.003	0.006	41505	64.0	4213	6.5
LP01	-0.023	-0.002	0.003	-0.003	0.016	0.004	0.004	0.047	0.007	0.003	0.007	61946	95.6	48815	75.3
LP03	-0.01	0.002	0.002	-0.004	0.014	0.003	-0.004	0.028	0.006	0.003	0.004	10552	16.3	5557	8.6
LPAL	-0.022	0.0	0.003	-0.0	0.018	0.002	-0.019	0.013	0.006	0.003	0.003	64241	99.1	21734	33.5
LRES	-0.0	0.017	0.002	-0.0	0.03	0.003	-0.017	0.02	0.008	0.003	0.004	64585	99.6	56428	87.1
TN01	-0.02	0.007	0.005	-0.026	0.016	0.007	-0.024	0.057	0.015	0.004	0.009	63347	97.7	31404	48.5
TN02	-0.013	0.005	0.003	-0.017	-0.001	0.003	-0.029	0.031	0.012	0.004	0.007	32371	49.9	17751	27.4
TN03	-0.009	0.015	0.004	-0.016	0.006	0.003	-0.021	0.027	0.008	0.003	0.004	15956	24.6	2948	4.5
TN06	-0.008	0.004	0.002	-0.015	0.005	0.003	-0.014	0.019	0.006	0.003	0.003	6226	9.6	0	0.0
TN09	-0.002	0.018	0.003	-0.018	-0.001	0.003	-0.015	0.022	0.008	0.003	0.004	61140	94.3	16001	24.7
TE11	-0.026	0.008	0.004	-0.018	0.004	0.003	-0.039	0.027	0.008	0.003	0.005	32891	50.7	5212	8.0
Mean	-0.012	0.009	0.003	-0.011	0.014	0.004	-0.024	0.027	0.009	0.003	0.005	43049.2	66.4	23950.9	37.0
Min/Max	-0.026	0.018	0.005	-0.026	0.03	0.007	-0.06	0.057	0.015	0.005	0.009	64697	99.8	57930	89.4

fixing statistic for network N32T

fixing percentage of	all GNSS	G	R	E	C
using threshold 0.3	95.0	95.4	94.3	95.4	94.6
considering satellites with dual-frequency fixed	93.0	93.7	92.0	93.3	92.4
considering all signals separately	93.2	93.7	92.0	93.9	92.0